



Warning: Illegal string offset 'small' in
/home/platne/serwer21911/public_html/copterx_pl/cache/3_1^%%5F^5F4^5F4AC088%%index.tpl.p
hp on line 18



CopterX (CX450EPP-FBL-V3) 450 Flybarless Electronic Parts Package V3

Features:

- Just add a radio system and battery of your choice to complete your CopterX CX450 class helicopter
- High quality mini / standard servos for extra weight saving
- ESC feature build-in BEC for simple and clean installation
- High power 3550KV motor for long and reliable operation

CX-9G Specification:

- Operating Voltage: 4.8VDC-6.0V DC
- Operating Speed: 0.17sec/60 4.8V
- Output Torque: >1.0kgf.cm(14.0oz.in)at 4.8V
- Weight: 9.0g(0.28oz)
- Dimensions: 22.5*12.8*23.7mm(0.89x0.5x0.93in)

MG-D-9257-V2 Specification:

- Wire: 25cm
- Operating Voltage: 4.8v - 6v
- Operating Speed: 0.09sec/60° (4.8V) / 0.08sec/60° (6.0V)
- Stall Torque: 2.2kg-cm (4.8V) / 2.4kg-cm (6.0V)
- Pulse width: 1520us
- Working Frequency: 333Hz
- Size: 36 x 15.2 x 29mm
- Weight: 25g

CX-3X2000 Features:

- Processing time 50 times faster than previous model
- Lightweight design will work with lightweight EP to large nitro helicopter
- Can operate as stabilizing system for quad and aeroplane with optional CopterX CX-PB002 USB cable
- Simply press button setup with multi LED display for quick and easy setup
- CNC aluminum alloy casing for vibration free and durable operation
- Control by high performance micro processor for accurate control for all direction
- Highly tunable and will work with most popular servos in the market
- Built-in one button setup for easy setup and operation
- Optional program box and USB setup cable available for detail fine tuning

CX-3X2000 Specification:

- Operating Voltage: DC 3.5V-9V
- Operating Current: 60mA
- Operating temperature: -15°C -65°C
- Maximum angular rate: 800 degrees / sec
- Support the rudder servo: 1.52ms analog servo, 1.52ms digital servos, 760us digital servos, 960us Digital Servo
- Support the swashplate servos: 1.52ms analog servo, 1.52ms digital servo
- Radio compatibility: PPM, PCM, 2.4G
- Supporting firmware upgrade

- Supporting Multi-blade roto head, Quad, airplane
- Weight: 20g (including cable and plug)
- Dimension: 39*26*13mm

CX-ESC-40A Specification:

- Cont. current: 40A
- Burst current(> 10s): 55A
- BEC mode: Linear
- BEC output: 5V / 3A
- BEC output capability: 5 servos (2S Lipo) / 4 servos (3S Lipo)
- Battery cell: 2-3S (Lipo) / 5-9 cells (NiMH)
- Weight: 39g
- Dimension: 68*25*8mm

Package Included:

- CopterX (CX-9G) 9G Servo X 3
- Fusonic (MG-D-9257-V2) 9257 25g Metal Gear High Speed Mini Digital Servo
- CopterX (CX-3X2000) Flybarless 3 Axis Gyro System
- CopterX (CX-ESC-40A) 40A V2 Brushless Electronic Speed Controller
- CopterX (CX450-10-04) 430XL Brushless Motor (3550KV)